

# 工程轮胎 OFF-THE-ROAD TYRE



C-1

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮廓 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOAD/KG
7.50-15 TT	6PR	C-1	6.00	-	785	215	400	1850
7.50-15 TL	12PR	C-1	6.00	-	785	215	750	2650
8.5/90-15 TL	6PR	C-1	6.00	-	785	220	345	1700
9.00-20 TT	12PR	C-1	7.0	-	1015	255	625	4000
11.00-20 TT	16PR	C-1	8.0	-	1080	290	725	5450
13/80-20 TT	16PR	C-1	8.5	-	1061	319	800	5430



C-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮廓 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOAD/KG
20.5-25 TT	16PR	C-2	17.00/2.0	16	1490	520	350	8250
23.1-26 TL	12PR	C-2	DW20	16	1500	595	200	5150
23.1-26 TT	12PR	C-2	DW20	16	1500	595	200	5150
23.1-26 TT	14PR	C-2	DW20	16	1500	595	230	5600



L-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮廓 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOAD/KG
12.5/70-16TL	6PR	L-2	10.00	16.5	848	316	200	1410
15.5/60-18TL	8PR	L-2	13.00	18	937	404	220	2195
15.5-25TL	12PR	L-2	12.00/1.3	23.5	1275	395	400	5600
17.5-25TL	12PR	L-2	14.00/1.5	26	1330	410	350	6150
17.5-25TT	12PR	L-2	14.00/1.5	26	1330	410	350	6150
17.5-25TL	16PR	L-2	14.00/1.5	26	1330	410	480	7300
20.5-25TL	16PR	L-2	17.00/2.0	29.5	1490	520	350	8250
23.5-25TT	16PR	L-2	19.50/2.5	31.5	1615	595	300	9500
23.5-25TL	16PR	L-2	19.50/2.5	31.5	1615	595	300	9500

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮廓 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOAD/KG
13.00-24TL	16PR	L-2	9.00DC	23.5	1300	350	400	3200
13.00-24TL	12PR	L-2	9.00DC	23.5	1300	350	300	2725
14.00-24TL	16PR	L-2	9.00DC	25	1370	375	350	3650
14.00-24TT	16PR	L-2	9.00DC	25	1370	375	350	3650
14.00-24TL	12PR	L-2	9.00DC	25	1370	375	250	3075
15.5-25TL	16PR	L-2	12.00/1.3	23.5	1275	395	325	3750
17.5-25TL	20PR	L-2	14.00/1.5	26	1330	410	400	5000

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮廓 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOAD/KG
8.25-16TT	14PR	L-3	6.50H	15	865	235	800	2300
16/70-20TT	10PR	L-3	13	23	1075	410	325	4250
16/70-20TT	14PR	L-3	13	23	1075	410	450	5150
16/70-20TL	14PR	L-3	13	23	1075	410	450	5150
16/70-24TT	10PR	L-3	13	23	1175	410	325	4750
16/70-24TT	14PR	L-3	13	23	1175	410	450	5600
17.5-25TT	12PR	L-3	14.00/1.5	26	1350	445	350	6150
17.5-25TT	12PR	L-3(JS)	14.00/1.5	32	1358	435	350	6150
17.5-25TT	16PR	L-3	14.00/1.5	26	1350	445	475	7300



L-3

# OFF-THE-ROAD TYRE 工程轮胎



# 工程轮胎 OFF-THE-ROAD TYRE

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
12.00-20TT	24PR	L5S	8.5	50	1173	315	900	6300
12.00-24TT	24PR	L5S	8.5	55	1275	315	975	7500
14.00-24TT	24PR	L5S	10.0	65	1420	375	850	9600
17.5-25TL	24PR	L5S	14.00/1.5	69	1400	445	675	9000
26.5-25TL	32PR	L5S	22.00/3.0	87.5	1800	675	550	17000
16.00-25TL	40PR	L5S	11.25/2.0	68	1550	430	1075	14500
16.00-25TL	32PR	L5S	11.25/2.0	68	1550	430	875	12500
18.00-25TL	40PR	L5S	13.00/2.5	75	1675	500	950	17000



L-5S



EV4

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
23.5-25 TL	20PR	EV4	19.50/2.5	44	1615	595	300	7300



E-3

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
15.5-25TL	12PR	E3	12.00/1.3	28.5	1275	385	250	3250
15.5-25TL	16PR	E3	12.00/1.3	23.5	1275	385	325	3750
17.5-25TL	12PR	E3	14.00/1.5	26	1340	420	225	3650
17.5-25TL	16PR	E3	14.00/1.5	26	1340	420	300	4250
17.5-25TL	20PR	E3	14.00/1.5	26	1340	420	400	5000
20.5-25TL	16PR	E3	17.00/2.0	29	1490	520	275	5450
20.5-25TL	20PR	E3	17.00/2.0	29	1490	520	325	6000
23.5-25TL	16PR	E3	19.50/2.5	30	1615	595	225	6150
23.5-25TL	18PR	E3	19.50/2.5	30	1615	595	300	7300
23.5-25TL	20PR	E3	19.50/2.5	30	1615	595	375	10900
26.5-25TL	24PR	E3	22.00/3.0	35	1750	675	400	14000
26.5-25TL	28PR	E3	22.00/3.0	35	1750	675	350	10000
26.5-25TL	32PR	E3	22.00/3.0	35	1750	675	550	17000
26.5-25TL	36PR	E3	22.00/3.0	35	1750	675	730	20000
29.5-25TL	28PR	E3	25.00/3.5	38	1875	750	325	11500
29.5-25TL	32PR	E3	25.00/3.5	38	1875	750	400	12800
29.5-29TL	28PR	E3	25.00/3.5	38	1975	750	325	12150



L-3

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
20.5-25TT	16PR	L-3	17.00/2.0	30	1490	520	350	8250
20.5-25TT	16PR	L-3(JS)	17.00/2.0	38	1506	536	350	8250
23.5-25TT	16PR	L-3	19.50/2.5	33	1615	595	300	9500
23.5-25TT	18PR	L-3	19.50/2.5	33	1615	595	335	10100
23.5-25TT	18PR	L-3(JS)	19.50/2.5	43	1615	595	335	10100
23.5-25TT	20PR	L-3	19.50/2.5	33	1615	595	375	10900
23.5-25TT	24PR	L-3	19.50/2.5	33	1615	595	475	12500
23.5-25TT	28PR	L-3	19.50/2.5	33	1615	595	550	13600
23.5-25TT	32PR	L-3	19.50/2.5	33	1615	595	700	15450
23.5-25TT	20PR	L-3(JD)	19.50/2.5	43	1673	613	375	10900
26.5-25TT	24PR	L-3(JS)	22.00/3.0	45	1760	675	400	14000



SL-3

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
17.5-25 TT	12PR	SL-3	14.00/1.5	28	1350	445	350	6150
23.5-25 TT	18PR	SL-3	19.50/2.5	33	1615	595	335	10100



KL-5

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
20.5-25 TL	20PR	KL-5	17.00/2.0	71.5	1550	520	450	9500
23.5-25 TL	20PR	KL-5	19.50/2.5	78.5	1675	595	375	10900
23.5-25 TL	24PR	KL-5	19.50/2.5	78.5	1675	595	475	12500



L-5

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
17.5-25 TL	16PR	L-5	14.00/1.5	63.5	1400	445	475	7300
17.5-25TT	20PR	L-5	14.00/1.5	63.5	1400	445	575	8250
20.5-25 TL	20PR	L-5	17.00/2.0	71.5	1550	520	450	9500
23.5-25 TL	20PR	L-5	19.50/2.5	78.5	1675	595	375	10900
26.5-25 TL	28PR	L-5	22.00/3.0	87.5	1800	675	475	15500
29.5-25 TL	28PR	L-5	25.00/3.5	95	1920	750	425	17500
29.5-25 TL	32PR	L-5	25.00/3.5	95	1920	750	500	19500



L-4

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
17.5-25 TL	16PR	L-4	14.00/1.5	46	1400	445	475	7300



G-6

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
13.00-25 TT	28PR	G-6	10.00/1.5	24.5	1300	350	1050	9250

规格 SIZE	层级 RR	花纹代码 PATTERN CODE	标准轮胎 STANDARD RM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELATIVE PRESSURE KPA	单胎负荷 MAX. LOADING KG
15.5-25TL	16PR	L-3/E-3	12.00/1.3	23.5	1275	385	325	3750
17.5-25TT	16PR	L-3/E-3	14.00/1.5	25	1340	420	300	4250
17.5-25TL	16PR	L-3/E-3	14.00/1.5	25	1340	420	300	4250
20.5-25TT	20PR	L-3/E-3	17.00/2.0	28	1490	520	325	6000
20.5-25TL	20PR	L-3/E-3	17.00/2.0	28	1490	520	325	6000
23.5-25TT	20PR	L-3/E-3	19.50/2.5	29.5	1615	595	300	7300
23.5-25TL	20PR	L-3/E-3	19.50/2.5	29.5	1615	595	300	7300
26.5-25TL	28PR	L-3/E-3	22.00/3.0	33	1750	673	350	10000
29.5-25TL	28PR	L-3/E-3	25.00/3.5	38	1875	735	325	11500



L-3/E-3

# 工程轮胎 OFF-THE-ROAD TYRE

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	50km/h 单胎负荷 MAX. LOADING KG
13.00-24 TT	18PR	NE3	10.00W	24	1301	351	450	3375
13.00-24 TL	18PR	NE3	10.00W	24	1301	351	450	3375
14.00-24 TT	24PR	NE3	10.00W	25.5	1368	375	575	5150
14.00-24 TL	24PR	NE3	10.00W	25.5	1368	375	575	5150
16.00-26 TL	32PR	NE3	11.25/2.0	28.5	1493	432	650	7300
17.5-25 TL	12PR	NE3	14.00/1.5	26	1350	445	225	3950
17.5-25 TT	12PR	NE3	14.00/1.5	26	1350	445	225	3950
17.5-25 TL	16PR	NE3	14.00/1.5	26	1350	445	300	4250
17.5-25 TT	16PR	NE3	14.00/1.5	26	1350	445	300	4250
20.5-25 TT	16PR	NE3	17.00/2.0	29	1490	520	275	5450
20.5-25 TL	16PR	NE3	17.00/2.0	29	1490	520	275	5450
20.5-25 TT	20PR	NE3	17.00/2.0	29	1490	520	325	6000
20.5-25 TL	20PR	NE3	17.00/2.0	29	1490	520	325	6000
23.5-25 TT	16PR	NE3	19.50/2.5	30	1615	595	225	6150
23.5-25 TL	16PR	NE3	19.50/2.5	30	1615	595	225	6150
23.5-25 TT	20PR	NE3	19.50/2.5	30	1615	595	300	7300
23.5-25 TL	20PR	NE3	19.50/2.5	30	1615	595	300	7300
26.5-25 TL	28PR	NE3	22.00/3.0	35	1750	675	350	10000
29.5-25 TL	28PR	NE3	25.00/3.5	38	1875	750	325	11600



NE3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
16/70-20 TT	14PR	R-5	13.00	25	1075	410	450	5150(10KM/H)
16/70-20 TL	18PR	R-5	13.00	25	1075	410	550	4500(30KM/H)



R-5

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
18.00-24 TT	12PR	R-6	13.00/2.5	25	1615	500	275	8250



R-6

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
18.00-25 TL	40PR	E-4B/E-4B PA	13.00/2.5	54	1675	500	950	17000



E-4B / E-4B PA

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
18.00-33 TL	36PR	E-4D	13.00/2.5	71	1875	500	850	18500
18.00-33 TL	40PR	E-4D/E-4D PA	13.00/2.5	71	1875	500	950	19500



E-4D / E-4D

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
12.00-20 TT	20PR	T17	8.5	22.5	1145	315	880	6100
14.00-20 TT	24PR	T17	10.0	25	1265	375	870	8500
14.00-24 TT	24PR	T17	10.0	25	1370	375	850	9500
14.00-24 TT	28PR	T17	10.0	25	1370	375	925	10000
14.00-25 TT	28PR	T17	10.0	25	1370	375	925	10000
14.00-25 TT	36PR	T17	10.0	25	1370	375	1200	11645

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	10km/h 标准气压 RELEVANT PRESSURE KPA	10km/h 单胎负荷 MAX. LOADING KG	50km/h 标准气压 RELEVANT PRESSURE KPA	50km/h 单胎负荷 MAX. LOADING KG
12.00-20 TT	20PR	E-3A	8.5	22.5	1145	315	825	6150	600	3450
14.00-20 TT	20PR	E-3A	10.0	25	1240	370	700	7500	525	4375
14.00-20 TT	24PR	E-3A	10.0	25	1240	370	850	8500	625	4875
14.00-24 TT	24PR	E-3A	10.0	25	1350	370	850	9500	575	5150
14.00-24 TT	28PR	E-3A	10.0	25	1350	370	925	10000	650	5600
14.00-24 TT	32PR	E-3A	10.0	25	1350	370	1050	10900	750	6150
14.00-25 TT	28PR	E-3A	10.0/1.5	24	1300	350	1050	9250	700	4875
13.00-25 TT	32PR	E-3A	10.0/1.5	24	1300	350	1200	10000	800	5300
14.00-25 TT	28PR	E-3A	10.0/2.0	25	1370	375	925	10000	650	5600
14.00-25 TT	36PR	E-3A	10.0/2.0	25	1370	375	1200	11500	850	6500



E-3A

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
10-16.5 TL	8PR	T1200	8.25	30	839	264	410	1880
10-16.5 TL	10PR	T1200	8.25	30	839	264	520	2135
12-16.5 TL	12PR	T1200	9.75	30	872	307	550	2865
10.5/80-18 TL	10PR	T1200	9.0	30	945	274	370	1950
12.5/80-18 TL	12PR	T1200	9.0	30	1015	308	370	2650
12.5/80-18 TL	14PR	T1200	9.0	30	985	308	430	2910
16.9-24 TL	14PR	T1200	DW15	24	1310	430	300	3530
16.9-28 TL	14PR	T1200	DW15	24	1435	430	300	3765
16.9-30 TL	14PR	T1200	DW15	24.5	1485	430	290	3705
19.5L-24 TL	12PR	T1200	DW16	29.5	1315	495	230	3450
21L-24 TL	14PR	T1200	DW18	32	1375	533	250	4200



T1200



TG-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
14.00-24 TL	16PR	TG-2	9.00DC	25	1348	362	350	3650



RG600A

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	30km/h 标准气压 RELEVANT PRESSURE KPA	30km/h 单胎负荷 MAX. LOADING KG
6.00-15 TT	10PR	RG600	4.50E	15	705	170	530	825
6.50-16 TT	14PR	RG600	5.50F	15	761	185	745	1250
7.00-16 TT	14PR	RG600	5.50F	17	785	200	745	1920
7.00-16 TT	16PR	RG600	5.50F	17	785	200	810	2020
7.50-16 TT	14PR	RG600	6.00G	12	815	215	745	2400
7.50-16 TT	16PR	RG600	6.00G	12	815	215	810	2490
8.25-16 TT	14PR	RG600	6.50H	14	865	235	800	2300
8.25-16 TT	16PR	RG600	6.50H	14	865	235	875	2400

## 工程子午轮胎 RADIAL OFF-THE-ROAD TYRE

规格 Size	原级 OR	花纹代码 PATTERN CODE	标准家宽 STANDARD WIDTH	帘布层数 PLY RATING	外直径 OUTER DIAMETER	断面宽 SECTION WIDTH	标准气压 STANDARD PRESSURE	100km/h 单轴负重 MAX LOAD @ 100 KM/H	标准气压 STANDARD PRESSURE	500km/h 单轴负重 MAX LOAD @ 500 KM/H
17.5R25	★	L-3 TT	14.00/1.5	25.5	1350	445	475	7100	350	4125
17.5R25	★	L-3 TL	14.00/1.5	25.5	1350	445	475	7100	350	4125
17.5R25	★★	L-3 TT	14.00/1.5	25.5	1350	445	600	8500	475	5450
17.5R25	★★	L-3 TL	14.00/1.5	25.5	1350	445	600	8500	475	5450
20.5R25	★	L-3 TT	17.00/2.0	30	1490	520	475	9500	350	5600
20.5R25	★	L-3 TL	17.00/2.0	30	1490	520	475	9500	350	5600
20.5R25	★★	L-3 TT	17.00/2.0	30	1490	520	600	11500	475	7300
20.5R25	★★	L-3 TL	17.00/2.0	30	1490	520	600	11500	475	7300
23.5R25	★	L-3 TT	19.50/2.5	33	1615	595	475	12150	350	7100
23.5R25	★	L-3 TL	19.50/2.5	33	1615	595	475	12150	350	7100
23.5R25	★★	L-3 TT	19.50/2.5	33	1615	595	600	14600	475	9250
23.5R25	★★	L-3 TL	19.50/2.5	33	1615	595	600	14600	475	9250



L-3 TT/TL

## INDUSTRIAL TYRE 工业轮胎



11  
ARMOUR TYRE



12  
ARMOUR TYRE